

1. DESCRIPTION OF REINFORCEMENT

NOTATION

THE SEQUENCE OF DESCRIPTION OF IDENTIFICATION MARKS ON DRAWINGS FOR STEEL REINFORCING BARS FOR CONCRETE WORK IS AS FOLLOWS :

NUMBER, TYPE, SIZE, MARK, SPACING, LOCATION OR COMMENT

ABBREVIATIONS

THE TYPE AND GRADE OF STEEL REINFORCEMENT TO BE USED AND ITS POSITION IN A STRUCTURE ARE DESCRIBED BY THE FOLLOWING ABBREVIATIONS :

X = PLAIN STEEL REINFORCING BARS IN GRADE 250

H = RIBBED STEEL REINFORCING BARS IN GRADE 500B

EW = EACH WAY

BW = BOTH WAY

EF = EACH FACE

BF = BOTH FACE

FF = FAR FACE

B = BOTTOM

NF = NEAR FACE

T = TOP

V = DIMENSIONS VARY

EXAMPLE

TO DESCRIBE 20 Nos. 16mm DIAMETER RIBBED STEEL REINFORCING BARS IN GRADE 500B, BAR MARK 63 AND AT 150mm SPACING AT THE TOP OF A SLAB, THE IDENTIFICATION MARK ON DRAWING SHALL BE :

20H16-63-150T

D	GENERAL REVISION	S.K. YEUNG	2/1/15
C	RE-FORMATTED TO CSWP	W.K. CHIU	14/11/03
B	GENERAL REVISION	W.K. CHIU	20/9/00
A	GENERAL REVISION	K.W. CHAN	16/2/96
REF.	REVISION	APPROVED	DATE

STANDARD SCHEDULING OF STEEL
REINFORCEMENT FOR CONCRETE



水務署
Water Supplies Department

APPROVED

G.C. LEE
AD/NW

DATE

9/6/92

SCALE

NOT APPLICABLE

DRAWING NO.

WSD 7.1D

CSWP